

Specifications

General

| | |
|-----------------|--|
| Recording media | SD card (512 MB – 2 GB) or SDHC card (4–32 GB) |
| File system | MTR partition: TASCAM original FAT partition: FAT32 |
| Microphones | 2 x Omni-directional condenser microphone |

Analogue inputs and outputs

| | |
|--|--|
| Inputs A and B, balanced | XLR |
| Nominal input impedance | 2.4 k Ω |
| Nominal input level | -16 dBu |
| Maximum input level | 0 dBu |
| Input A, balanced | 6.3-mm TRS jack |
| When INPUT A switch is set to MIC/LINE | |
| Nominal input impedance | ≥ 10 k Ω |
| Nominal input level | +4 dBu |
| Maximum input level | +24 dBu |
| When INPUT A switch is set to GUITAR | |
| Nominal input impedance | ≥ 1 M Ω |
| Nominal input level | -2 dBV |
| Maximum input level | +14 dBV |
| Input B, balanced | 6.3-mm TRS jack |
| Nominal input impedance | ≥ 10 k Ω |
| Nominal input level | +4 dBu |
| Maximum input level | +24 dBu |
| Line Output | RCA (unbalanced) |
| Nominal output impedance | 1 k Ω |
| Nominal output level | -10 dBV |
| Maximum output level | +6 dBV |
| Phones Output | 6.3-mm stereo jack |
| Maximum output power | 40 mW + 40 mW (THD+N: ≤ 0.1 %, into 32 Ω) |

Other inputs and outputs

| | |
|-------------|--|
| USB port | Mini-B type USB connector |
| Format | USB 2.0 HIGH SPEED, mass storage class |
| REMOTE port | 2.5-mm jack (for RC-3F footswitch) |

Audio performance

| | |
|---------------------------|-----------------------------|
| Frequency response | 20 Hz – 20 kHz, +1 dB/-3 dB |
| Signal-to-noise ratio | ≥ 90 dB |
| Total harmonic distortion | ≤ 0.01 % |

Power supply and other specifications

| | |
|-----------------------------|-----------------------------|
| External power adapter | TASCAM PS-1225L (included) |
| AC input | 100–240 V AC, 50/60 Hz, 1 A |
| DC output | 12 V, 2.5 A |
| Power consumption | 5 W |
| Dimensions (W x H x D) | 290 mm x 54 mm x 207 mm |
| Weight | 1.4 kg |
| Operating temperature range | 5–35 $^{\circ}$ C |