

Evoked Technical Data

Model	Evoked 1200			
Rated Power	1200W			
Input Voltage/Current	DC48V/25A Max, AC100-240V 50/60Hz			
CRI	96			
TLCI	97			
CCT	5600K			
Dimming	0-100% in ultra-precise intervals of just 0.1%			
IP Rating	IP54			
Control	On-board controller, 2.4G, Bluetooth, DMX, RDM, LumenRadio, Wire Control			
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding			
Product Size	Light Fixture (without Yoke): 330×241×210mm / 12.99×9.48×8.26" Light Fixture (with Yoke): 503×370×210mm / 19.8×14.56×8.26" Power Supply: 376.5×181×246mm / 14.82×7.12×9.68"			
Product Weight	Light Fixture: 6.94kg/15.3lb Yoke: 1.84kg/4.05lb Power Supply: 10.5kg/23.14lb			
Configuration	Evoked 1200×1 Yoke×1 Power Supply×1 Reflector×1 DC Connection Cable 7.5M×1 AC Power Cable 6M×1 AS-CP-QR-EV Evoked Quick Release Clamp×1 USB Flash Drive×1 WS-RC-C2 Remote Controller×1 User Manual×1 DMX Reference Guide×1 Thank You Card×1			
Certifications	CE, UKCA, PSE, KCC, ROHS, KUCAS, FCC-ID			

illumination (lux / fc)

CCT	5600K			
Distance	3M	5M	7M	10M
Light Only	5532 lux / 514 fc	2373 lux / 220 fc	1266 lux / 118 fc	679 lux / 63 fc
With Reflector	18460 lux / 1715 fc	6583 lux / 612 fc	3671 lux / 341 fc	2021 lux / 188 fc
With Fresnel Lens 11°	65280 lux / 6065 fc	22080 lux / 2051 fc	11765 lux / 1093 fc	6308 lux / 586 fc
With Fresnel Lens 30°	25560 lux / 2375 fc	10640 lux / 988 fc	5674 lux / 527 fc	3043 lux / 283 fc
With Fresnel Lens 45°	15170 lux / 1409 fc	5718 lux / 531 fc	3065 lux / 285 fc	1644 lux / 153 fc