

Product Name



Kandao Meeting Ultra Standard

Main Device	Length	215mm
	Width	121mm
	Height	327mm
	Weight	2161g
Remote Controller	Height	160mm
	Width	42mm
	Thickness	21mm
Compatibility	System Requirements	Windows 7 or later, MacOS 10.8 or later
	Compatible Platforms	Teams, Zoom, Tencent Meeting, Google Meet, GotoMeeting, Skype, BlueJeans, DingTalk, Slack, Polycom, StarLeaf, Cisco Webex, 云视讯, 华为云会议, 沃畅云会议, 天翼云会议 and more
Camera	Resolution @ Frame Rate	3840*2160@30fps 1920*1080@30fps 1280*720@30fps
	Encoding Format	MJPEG / H264
Microphone	Quantity	Eight Omni-directional beamforming microphones
	Pickup Range	5.5m
	Sensitivity	-38dB+/-1dB@1KHz
	Acoustic Echo Cancellation	Supported
	Voice Enhancement	Supported
Speaker	Noise Cancellation	Supported
	Power	10W
Ports and Interfaces	USB C	USB Type C Out x 1: USB 3.1, connect to computer for transmitting audio/video (UVC/UAC)
		USB Type C In x 1: for power supply
	Ethernet	RJ45 x 1: Gigabit Ethernet port for wired network transmission, and PoE power supply
	USB A	USB A x 3: for connect with peripherals, such as mouse and keyboard
	HDMI	HDMI OUT 2.1 x 2: Video output, displaying system interface
		HDMI IN 2.0 x 1: HDMI 2.0, Video input for screen sharing from a computer
	Wi-Fi	2.4G + 5G, Wi-Fi 6
	Bluetooth	Bluetooth 5.0
Device Lock Hole	for Kensington Security Lock	
Screw Hole	1/4 inch	
Storage	System Memory	64G
	Micro SD Card	Support FAT32 and exFat format. (Up to 1TGB)
Power Supply	Adapter	Input: AC100-240V 50/60Hz 0.45A max Output: DC 15V 3A
	PoE	Support IEEE802.3bt; 44-58V 1A