

LUMIX S Lens S-R24105

Features	Lens Construction	16 elements in 13 groups (2 aspherical ED lenses, 2 aspherical lenses, 1 UED lens, 2 ED lenses)
	Mount	L-Mount
	Optical Image Stabilizer	yes
	Focal Length	f=24-105mm
	Aperture Type	9 diaphragm blades / Circular aperture diaphragm
	Maximum Aperture	F4.0
	Minimum Aperture	F22
	Closest Focusing Distance	0.30m / 0.98ft
	Maximum magnification	Approx. 0.5x
General	Diagonal Angle of View	84°(Wide) - 23°(Tele)
	Dust and Splash Resistant	Yes*
	Recommended Operating Temperature	-10oC to 40oC (14oF to 104oF)
	Filter Size	φ77mm
	Max. Diameter	φ84mm / 3.31inch
	Overall Length	Approx. 118mm / 4.65inch (from the tip of the lens to the base side of the lens mount)
	Weight [g]	Approx. 680g (excluding lens cap, lens rear cap and lens hood)
	Weight [oz]	Approx. 23.99oz (excluding lens cap, lens rear cap and lens hood)
Standard Accessories		Lens cap, Lens rear cap, Lens hood, Lens storage bag
NOTE		*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.