LUMIX S PRO Lens S-X50

Features	Lens Construction	13 elements in 11 groups (2 aspherical lenses, 3 ED lenses)
	Mount	L-Mount
	Optical Image Stabilizer	-
	Focal Length	f=50mm
	Aperture Type	11 diaphragm blades / Circular aperture diaphragm
	Maximum Aperture	F1.4
	Minimum Aperture	F16
	Closest Focusing Distance	0.44m / 1.44ft
	Maximum magnification	Approx. 0.15x
General	Diagonal Angle of View	47°
	Dust and Splash Resistant	Yes*
	Recommended Operating Temperature	-10oC to 40oC (14oF to 104oF)
	Filter Size	φ77mm
	Max. Diameter	φ90mm / 3.54inch
	Overall Length	Approx. 130mm / 5.12inch (from the tip of the lens to the base side of the lens mount)
	Weight [g]	Approx. 955g (excluding lens cap, lens rear cap and lens hood)
	Weight [oz]	Approx. 33.69oz (excluding lens cap, lens rear cap and lens hood)
Standard Accessories		Lens cap, Lens rear cap, Lens hood, Lens storage bag
NOTE		*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

Copyright © 2019 Panasonic