

Technical Specifications RGBlink RGMINIP2

Connections:

- Input: 1x HDMI2.0, 3x HDMI 1.3 (HDMI-A)
- Output: 1x HDMI 1.3 (HDMI-A), 1x USB 3.0, 1x USB 2.0 (Type A)
- Audio: je 1x 3.5mm Stereo Klinke Ein-/Ausgang
- Network: 1x RJ45 LAN
- Powersupply: DC 12V/1.5A, max 18W

Resolution Input:

- SMPTE: 720p50/60 | 1080i50 | 1080p23/24/30/50/60 | 2160p@60
- Vesa: 1024x768@60 | 1280x720@60 | 1280x768@60 | 1280x800@60 | 1280x1024@60 | 1360x768@60 | 1366x768@60 | 1440x900@60 | 1600x1200@60 | 1680x1050@60 | 1920x1080@60 | 1920x1200@60 | 3480x2160@60 | 4096x2160@60

Resolution Output:

- SMPTE: 720p60 | 1080p60
- Vesa: 1024x768@60 | 1280x720@60 | 1280x768@60 | 1280x1024@60 | 1360x768@60 | 1900x1200@24/25/30/50/60

Supported Standards:

- HDMI 2.0, USB 3.0, ITU-T H.265 / ISO / IEC 23008-2

Supported Protocol:

- PTZ: VISCA

Colorspace and Sampling

- RGB 4:4:4 YUV

Powersupply:

- 12V/1.5A, max. 18W

Dimensions:

- 180mm x 118mm x 58mm (l/b/h)
- 420g net. weight