

Specifications

Stabilizer

Tilt Mechanical Range	310°
Roll Mechanical Range	340°
Pan Mechanical Range	360°

Battery

Operation Voltage	Max: 12.6v / Min: 9.8v
Operation Current	Max: 6000mA / Min: 160mA
Output	5V, 1A
Battery Runtime	Max: 21h (lab data)
Charging Time	2h (lab data)

Size & Weight

Product Size (W*D*H)	342*207*73mm
Net Weight	~1130g/unit

Camera Compatibility List

Sony	A1; A9II; A9; A7R4; A7M4; ILME-FX3; A7R3; A7M3; A7S3; A7R2; A7M2; A7S2; A7C; ZV-E10; A6600; A6500; A6400; A6300; A6100
Nikon	D850; D780; Z5; Z6; Z6II; Z7; Z7II; Z30; Z50; ZFC
Canon	5D MARK III; 5D MARK IV; 5DS; 5DS R; 6D MARK II; 80D; 90D; M50; EOS M6 MARK II; EOS R5; EOS R6; EOS R7; EOS R10; EOS R; EOS RP;
Panasonic	G9; GH5; GH5S; S5; GH6; DC-BGH1
OLYMPUS	OM-DE-M1 MARK II
FUJIFILM	X-T3; XT-4; X-H2S
ZCAM	E2
SIGMA	FP